

Power

FXM 2000 Rugged UPS Module



- 2000W/VA UPS designed to operate in extreme environments and provide maximum flexibility while ensuring critical loads remain protected and running during power outages and other power disturbances
- Wide range Automatic Voltage Regulation (AVR) lengthens battery life by providing protection without transferring to backup mode during voltage surge or sag
- Independently programmable control and reporting dry contacts allow monitoring and controlling of key functions
- Temperature compensated battery charging protects batteries from overcharging or undercharging at extreme temperatures, extending the life of the battery
- Local and remote monitoring and control via RS232 port and Ethernet SNMP interface*
- UPS panels can be rotated, improving flexibility and viewing convenience

Alpha FXM is a line of rugged UPS power modules used worldwide where clean backup power is needed. Designed to perform in the most extreme demanding environments, Alpha FXM units ensure equipment in security, communications, traffic, industrial environments, and many other critical applications remains safe and protected from power disturbances. Thanks to its powerful programmable battery charger, the FXM is capable of providing the runtime you need. All FXM models are available in 120Vac and 230Vac.

*Ethernet SNMP card is standard on the 120Vac model and optional on the 230Vac model

FXM 2000 Rugged UPS Module

Consult your Alpha representative for P/N configurations

Electrical

> 120Vac Model

Battery string voltage: 48Vdc
 Nominal voltage: 120Vac
 Frequency: 60Hz/50Hz \pm 5% (auto detection)
Input:
 Voltage range: 85 to 152Vac
 Current: 20A (@ nominal voltage and max battery charging current)

Output:
 Waveform: Pure sinewave
 Nominal voltage: 120Vac
 Voltage regulation: \pm 10% over input voltage range
 Power at 50°C: 2000W/VA
 Frequency: Output frequency = input frequency

> 230Vac Model

Battery string voltage: 48Vdc
 Nominal voltage: 230Vac
 Frequency: 60Hz/50Hz \pm 5% (auto detection)
Input:
 Current: 12A (@ nominal voltage and max battery charging current)
 Voltage range: 150 to 328Vac

Output:
 Waveform: Pure sinewave
 Nominal voltage: 230Vac
 Voltage regulation \pm 10% over input voltage range
 Power at 55°C: 2000W/VA
 Frequency: Output frequency = input frequency

Mechanical

Dimensions:
 mm: 133H x 394W x 222D
 inches: 5.22H x 15.5W x 8.75D
Weight: 16kg (35lbs)

Environmental



Operating temp range*: -40 to 74°C (-40 to 165°F)
 Audible noise @ 25°C: 45dBa @ 1 meter (39in)
 *120Vac module derates after 50°C (122°F). 230Vac module derates after 55°C (131°F)

Performance


Typical output voltage THD: <3%
 Typical efficiency: >98% (resistive load)
 Typical transfer time: <5ms

Power Connector Options

120Vac Model

	Input	Output
Standard	 Terminal Block	 Terminal Block

230Vac Model

Standard	 Terminal Block	 Terminal Block
----------	---	--

Agency Compliance

Electrical safety: UL1778, CSA 22.2 No 107.3; EN62040-1

Marks:  

EMC: CFR47, Part 15 Subpart B, Class A;
 CES-003 Class A; EN62040-2

**CE applies to 230Vac version only