


Bimetallic steam trap

ANSI 150 / 300

- with flanges (Series 600/601...1)
- with threaded ends (Series 600/601...2)
- with socket weld ends (Series 600/601...3)
- with butt weld ends (Series 600/601...4)




Forged steel
Series 600

Page 2

High pressure - Bimetallic steam trap

ANSI 400 / 600

- with flanges (Series 600/601...1)
- with socket weld ends (Series 600/601...3)
- with butt weld ends (Series 600/601...4)



High temperature steel
1/2"-1"
Series 600

Page 4
1 1/2"-2"
Page 6





Fig. 600...1

High pressure - Bimetallic steam trap

ANSI 900 / 1500

- with flanges (Series 600/601...1)
- with socket weld ends (Series 600/601...3)
- with butt weld ends (Series 600/601...4)




High temperature steel
Series 600

Page 6

High pressure - Bimetallic steam trap

ANSI 2500

- with flanges (Series 600/601...1)
- with socket weld ends (Series 600/601...3)
- with butt weld ends (Series 600/601...4)



High temperature steel
Series 600

Page 8

Features:

- For the discharge of condensate sub-cooled up to 30 K / 54 °F
- Automatic ventilation during start up and operation of the plant
- Robust and insensitive to water hammer
- Integrated check valve
- Design:
 - with integrated strainer - Series 600
 - with outside strainer - Series 601 (Y)
- Optimized design for quick installation (ANSI 150 / 300, size 1/2"-1")
- Machined sealing surface (body to cap) (ANSI 150 / 300, size 1/2"-1")
- Installation with cover facing up or sideways
- Subcooling of condensate is continuously adjustable (observe the operation instructions)
- The exchange of the controller is possible without disturbing the pipe connections
- CRN approved

Selection criteria:

- | | |
|--------------------------|--|
| - Steam pressure | - Type of connection |
| - Back pressure | - Controller |
| - Quantity of condensate | - Material |
| - Size / Class | - Place of service or type of steam consumer |

Example for order data:

45.600 / type of connection / size / controller

=> Bimetallic steam trap CONA® B - Figure 45.600,
SA105, ANSI 300, with flanged connection,
Size 1", Controller R22, Face-to-face dimension 6.30 inch

Bimetallic steam trap made of forged steel




Fig. 600/601....2 threaded ends




Fig. 600/601....1 flanged




Fig. 600/601....3 socket welded ends





Fig. 600/601....4 butt welded ends

- Bimetallic steam trap with corrosion resistant and water hammer proof bimetallic controller
- Automatic ventilation during start up and operation of the plant
- Integrated check valve
- with integrated strainer - Series 600 with outside strainer - Series 601 (Y)
- Optimized design for quick installation
- Installation with cover facing up-or sideways
- Subcooling of condensate is continuously adjustable (observe the operation instructions)
- Service advantage machined mating cap to body

ANSI 150 ANSI 300 SA 105	Fig. 42.600/601 Fig. 45.600/601	Operating limits		
Max. temperature (°F) ANSI 150		n.a.	n.a.	437
Max. temperature (°F) ANSI 300		771	800	800
Controller unit permissible ΔP (psi)	Sizes 1/2" to 2"	R32 464	R22 319	R13 189

Types of connection

Flanges1	ANSI 150 RF and 300 RF
Threaded ends2	R- and NPT-thread
Socket weld ends3	
Butt weld ends4	
Other types of connection on request.	



Dimensions and weights	Types of connection														
	Flanges					Threaded ends Socket weld ends					Butt weld ends				
Size	1/2"	3/4"	1"	1 1/2"	2"	1/2"	3/4"	1"	1 1/2"	2"	1/2"	3/4"	1"	1 1/2"	2"
Dimensions (in)	L *	5.91	5.91	6.30	9.06	9.06	3.74	3.74	3.74	6.3/ 5.12	8.27	9.84	9.84	9.84	9.84
	H	3.86	3.86	3.86	5.67	5.67	3.86	3.86	4.06	5.67	5.67	3.86	3.86	5.67	5.67
	H1	2.44	2.44	2.44	2.68	2.68	2.44	2.44	2.17	2.68	2.68	2.44	2.44	2.68	2.68
Weight approximate (lb)	7.1	8.2	9.3	24.9	26.7	3.7	3.5	4.6	17.6	17.6	4.9	5.1	5.3	19.6	21.6

* other face-to-face dimensions on request

For standard flange dimensions refer to page 10


Parts

Pos.	Description	Material codes
		ASTM / AISI
1	Body	SA 105
2	Strainer *	SA 240 Gr. 304
6	Screw cap	SA 105
7 (Y)	Strainer screen *	SA 240 Gr. 304
8 (Y)	Strainer plug *	SA 182 F321
24	Controller *	corrosion resist. bimetal TB 102 / 85
42	Sealing ring for plug*	R-Cu99
43	Plug *	1035, 1038 ¹⁾
46	Blow down valve cpl.	AISI 303

* Spare parts

Design parameters acc. ASME B16.34

¹⁾ with metric screw-thread

Capacity chart

Capacity chart

The capacity chart shows the maximum flow for controller R13, R22 and R32 at factory setting.

Curve 1

Maximum flow rate of hot condensate at approx. 10 K / 18°F below saturation temperature.



Curve 2

Maximum flow rate of sub-cooled condensate approx. 30 K / 54°F below saturation temperature.

Curve 3

Maximum flow rate of condensate at about 68°F (cold start-up).

The condensate-temperature determines the opening of the controller. The capacity increases with sub-cooling of the condensate.



Series 601 (Y) with outside strainer

Optional: with blow down valve

High pressure - Bimetallic steam trap made of high temperature steel





Fig. 600....4 butt welded ends

Fig. 600....3
socket welded ends



- Bimetallic steam trap with corrosion resistant and water hammer proof bimetallic controller
- Automatic ventilation during start up and operation of the plant
- Integrated check valve
- Integrated strainer
- Installation with cover facing up-or sideways
- Subcooling of condensate is continuously adjustable (observe the operation instructions)
- The exchange of the controller is possible without disturbing the pipe connections
- Controller at ANSI 600 available for operating range:
 - Controller R56 - up to 812 psi inlet pressure
 - Controller R90 - up to 1203 psi inlet pressure

ANSI 400 SA 182 F12	Fig. 86.600	Operating limits
Max. temperature (°F)		816
Controller unit permissible ΔP (psi)	Sizes 1/2" to 1"	R46 667

ANSI 600 SA 182 F12	Fig. 87.600	Operating limits
Max. temperature (°F)		917
Controller unit permissible ΔP (psi)	Sizes 1/2" to 1"	R56 812


Types of connection		
Flanges1	ANSI 400/600 RF	ANSI 600 RF
Socket weld ends3		
Butt weld ends4		
Other types of connection on request.		

Dimensions and weights		Types of connection								
		Flanges			Socket weld ends			Butt weld ends		
Size		1/2"	3/4"	1"	1/2"	3/4"	1"	1/2"	3/4"	1"
Dimensions (in)	L *	8.27	8.27	9.06	6.30	6.30	6.30	6.30	6.30	6.30
	H	4.09	4.09	4.09	4.09	4.09	4.09	4.09	4.09	4.09
	H1	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65
Weight approximate (lb)		13.7	14.3	20.5	10.1	9.9	9.7	10.1	9.9	9.7
* other face-to-face dimensions on request		For standard flange dimensions refer to page 10					larger sizes (ANSI600) refer to page 6			

Parts

Pos.	Description	Material codes
		ASTM / AISI
1	Body	SA 182 F12
2	Strainer *	SA 240 Gr. 304
6	Cover	SA 182 F12
24	Controller *	corrosion resistant bimetal TB 102 / 85
26	Body-gasket *	CrNi laminated both sides with pure graphite
28	Hexagonal nuts	SA 193 Gr. 4 ¹⁾
29	Erosion deflector *	AISI 431
30	Extension sleeve	SA 193 Gr. B16
36	Studs	SA 193 Gr. B16 ¹⁾

* Spare parts Design parameters acc. ASME B16.34 ¹⁾ with metric screw-thread

Capacity chart

Capacity chart

The capacity chart shows the maximum flow at factory setting.
(Other factory settings for the sub-cooling on request.)

Curve 1

Maximum flow rate of condensate at factories setting about approx. ΔT 15 K / 27 °F below saturation temperature.

Curve 2

Maximum flow rate of condensate sub-cooling at ΔT approx. 30 K / 54°F.

Curve 3

Maximum flow rate of condensate at about 68°F (cold start-up).

The condensate temperature determines the opening of the controller. The capacity increases with sub-cooling of the condensate.

High pressure - Bimetallic steam trap made of high temperature steel




Fig. 600....4 butt welded ends






Fig. 600....1
with flanges

Fig. 600....3
socket welded ends




Dimensions and weights		Types of connection							
		Flanges		Socket weld ends			Butt weld ends		
Size		1/2"	1"	1/2"	3/4"	1"	1/2"	3/4"	1"
Dimensions (in)	L *	8.27	9.06	6.30	6.30	6.30	6.30	6.30	6.30
	H	4.09	4.09	4.09	4.09	4.09	4.09	4.09	4.09
	H1	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65
Weight approximate (lb)		14.1	21.2	10.6	10.4	10.1	10.6	10.4	10.1
* other face-to-face dimensions on request					For standard flange dimensions refer to page 10				

Parts

Pos.	Description	Material codes	
		ASTM / AISI (ANSI 900)	ASTM / AISI (ANSI 1500)
1	Body	SA 182 F12	SA 182 F22 (SA 182 F91 on request)
2	Strainer *	SA 240 Gr. 304	SA 240 Gr. 304
6	Cover	SA 182 F12	SA 182 F22
24	Controller *	corrosion resistant bimetal TB 102 / 85	corrosion resistant bimetal TB 102 / 85
26	Gasket (body/cover) *	CrNi laminated both sides with pure graphite	CrNi laminated both sides with pure graphite
28	Hexagonal nuts	SA 193 Gr. B16 ¹⁾	SA 193 Gr. B16 ¹⁾
29	Erosion deflector *	AISI 303	AISI 303
30	Extension sleeves	SA 193 Gr. B16	SA 193 Gr. B16
32	Clamping sleeve *	AISI 303	AISI 303
36	Studs	SA 193 Gr. B16 ¹⁾	SA 193 Gr. B16 ¹⁾

* Spare parts Design parameters acc. ASME B16.34 ¹⁾ with metric screw-thread

Capacity chart ANSI 900

Capacity chart

The capacity chart shows the maximum flow of hot and cold condensate at factory setting.
(Other factory settings for the condensate sub-cooling on request.)

Curve 1


Maximum flow rate of hot condensate at approx. 10 K / 18°F below saturation temperature.

Curve 2

Maximum flow rate of hot condensate at approx. 30 K / 54°F below saturation temperature.

Curve 3

Maximum flow rate of condensate at about 68°F (cold start-up).

Capacity chart ANSI 1500


High pressure - Bimetallic steam trap made of high temperature steel




Fig. 600....4 butt welded ends

- Bimetallic steam trap with corrosion resistant and water hammer proof bimetallic controller
- Automatic ventilation during start up and operation of the plant
- Integrated check valve
- Integrated strainer
- Installation with cover facing up-or sideways
- Subcooling of condensate is continuously adjustable (observe the operation instructions)
- The exchange of the controller is possible without disturbing the pipe connections

ANSI2500 Fig. 8c.600 SA 182 F22		Operating limits
Max. temperature (°F)		873
Controller unit permissible ΔP (psi)	Sizes 1/2" to 1"	R270 3915

ANSI 2500 Fig. 8c.600 SA 182 F91		Operating limits
Max. temperature (°F)		873
Controller unit permissible ΔP (psi)	Sizes 1/2" to 1"	R270 3915






Fig. 600....1
flanged

Fig. 600....3
socket welded ends

Types of connection

Flanges1	ANSI 2500 RF
Socket weld ends3	DIN EN 12670, ANSI B16.11
Butt weld ends4	DIN EN 12627, ANSI B16.25
Other types of connection on request.	



Dimensions and weights		Types of connection					
		Flanges		Socket weld ends		Butt weld ends	
Size	L *	1/2"	1"	1/2"	1"	1/2"	1"
Dimensions (in)	L *	17.13	18.50	12.99	12.99	12.99	12.99
	H	5.32	5.32	5.32	5.32	5.32	5.32
	H1	2.48	2.48	2.48	2.48	2.48	2.48
Weight approximate (lb)		59.5	72.8	44.1	41.9	44.1	41.9

* other face-to-face dimensions on request


For standard flange dimensions refer to page 10.

Parts

Pos.	Description	Material codes	
		ASTM / AISI	ASTM / AISI
1	Body	SA 182 F22	SA 182 F91
2	Strainer *	SA 240 Gr.304	SA 240 Gr.304
6	Cover	SA 182 F22	SA 182 F91
24	Controller *	corrosion resistant bimetal TB 102 / 85	corrosion resistant bimetal TB 102 / 85
26	Gasket (body/cover) *	Spiral-wound gasket	Spiral-wound gasket
28	Hexagonal nuts	SA 453 Gr. 660 b ¹⁾	SA 453 Gr. 660 b ¹⁾
29	Erosion deflector *	AISI 303	AISI 303
31	Baffle straightener	AISI 440	AISI 440
32	Clamping sleeve *	AISI 303	AISI 303
36	Studs	SA 453 Gr. 660 b ¹⁾	SA 453 Gr. 660 b ¹⁾

* Spare parts

Design parameters acc. ASME B16.34

¹⁾ with metric screw-thread
Capacity chart ANSI 2500

Capacity chart

The capacity chart shows the maximum flow rate of hot and cold condensate at factory setting.
 (Other factory settings for the condensate sub-cooling on request.)

Curve 1

Maximum flow rate of hot condensate at approx. 10 K / 18°F below saturation temperature.

Curve 2

Maximum flow rate of hot condensate at approx. 30 K / 54°F below saturation temperature.

Curve 3

Maximum flow rate at cold condensate at about 68°F (cold start-up).

Flange dimensions (DIN)

Size	PN 16 bar			PN 40 bar			PN 63 bar			PN 100 bar		
	Ø D	Ø K	n x Ø d1	Ø D	Ø K	n x Ø d1	Ø D	Ø K	n x Ø d1	Ø D	Ø K	n x Ø d1
1/2"	3.74	2.56	4 x 0.55	3.74	2.56	4 x 0.55	4.13	2.95	4 x 0.55	4.13	2.95	4 x 0.55
3/4"	4.13	2.95	4 x 0.55	4.13	2.95	4 x 0.55	--	--	--	--	--	--
1"	4.53	3.35	4 x 0.55	4.53	3.35	4 x 0.55	5.51	3.94	4 x 0.71	5.51	3.94	4 x 0.71
1 1/4"	5.51	3.94	4 x 0.71	5.51	3.94	4 x 0.71	--	--	--	--	--	--
1 1/2"	5.91	4.33	4 x 0.71	5.91	4.33	4 x 0.71	6.69	4.92	4 x 0.87	6.69	4.92	4 x 0.87
2"	6.50	4.92	4 x 0.71	6.50	4.92	4 x 0.71	7.09	5.31	4 x 0.87	7.68	5.71	4 x 1.02

Size	PN 160 bar			PN 250								
	Ø D	Ø K	n x Ø d1	Ø D	Ø K	n x Ø d						
1/2"	5.12	2.95	4 x 0.55	130	90	4 x 18						
1"	5.91	3.94	4 x 0.71	--	--	--						
2"	7.68	5.71	4 x 1.02	150	105	4 x 22						

Flange dimensions (ANSI)

Size	ANSI 150			ANSI 300			ANSI 400		
	Ø D	Ø K	n x Ø d	Ø D	Ø K	n x Ø d	Ø D	Ø K	n x Ø d
in	in	in	in	in	in	in	in	in	in
1/2"	3.50	2.36	4 x 0.62	3.75	2.62	4 x 0.62	3.75	2.62	4 x 0.62
3/4"	3.90	2.70	4 x 0.62	4.62	3.25	4 x 0.75	4.62	3.25	4 x 0.75
1"	4.25	3.10	4 x 0.62	4.88	3.50	4 x 0.75	4.88	3.50	4 x 0.75
1 1/4"	4.62	3.50	4 x 0.62	5.25	3.88	4 x 0.75	--	--	--
1 1/2"	5.00	3.85	4 x 0.62	6.12	4.50	4 x 0.88	--	--	--
2"	6.00	4.76	4 x 0.75	6.50	5.00	8 x 0.75	--	--	--

Size	ANSI 600			ANSI 900			ANSI 1500			ANSI 2500		
	Ø D	Ø K	n x Ø d	Ø D	Ø K	n x Ø d	Ø D	Ø K	n x Ø d	Ø D	Ø K	n x Ø d
in	in	in	in	in	in	in	in	in	in	in	in	in
1/2"	3.75	2.62	4 x 0.62	4.75	3.25	4 x 0.88	4.75	3.25	4 x 0.88	5.25	3.50	4 x 0.88
3/4"	4.62	3.25	4 x 0.75	5.12	3.50	4 x 0.88	5.12	3.50	4 x 0.88	5.5	3.75	4 x 0.88
1"	4.88	3.50	4 x 0.75	5.88	4.00	4 x 1.0	5.88	4.00	4 x 1.0	6.25	4.25	4 x 1.0
1 1/4"	5.25	3.88	4 x 0.75	6.25	4.38	4 x 1.0	--	--	--	--	--	--
1 1/2"	6.12	4.50	4 x 0.88	7.00	4.88	4 x 1.12	--	--	--	--	--	--
2"	6.50	5.00	8 x 0.75	8.50	6.50	8 x 1.0	--	--	--	--	--	--

Steam traps according to ASTM

- Pressure bearing parts made of ASTM / AISI -materials
- Studs and nuts made of ASTM-materials, but metric screw-threads
- Face-to-face acc. to data sheet resp. customer request
- Flanges acc. to ANSI
- Pressure test acc. to API 598



Technology for the Future.
GERMAN QUALITY VALVES

ARI-Armaturen, USA Inc., 9363 Winkler Drive, Suite A, Houston, Texas 77017, USA,
Phone 713.947.3622 Fax 713.947.3635, Internet: <http://www.ari-armaturen.com> E-mail: scris@usa.ari-armaturen.com